



BARRAS DE COBRE

Dimensiones Diámetro ó Distancia entre caras paralelas		PESOS					
		REDONDO		EXAGONAL		CUADRADO	
en plgs	en mm	KG / M	LBS / PIE	KG / M	LBS / PIE	KG / M	LBS / PIE
1/8	3.175	0.070	0.047	0.078	0.052	0.090	0.060
3/16	4.763	0.158	0.106	0.175	0.118	0.202	0.136
7/32	5.556	0.215	0.144	0.238	0.160	0.275	0.185
1/4	6.350	0.282	0.190	0.311	0.209	0.359	0.241
5/16	7.938	0.441	0.296	0.486	0.327	0.561	0.377
3/8	9.525	0.633	0.425	0.700	0.470	0.808	0.543
7/16	11.113	0.861	0.578	0.953	0.640	1.100	0.739
1/2	12.700	1.126	0.755	1.242	0.833	1.437	0.963
9/16	14.288	1.424	0.955	1.576	1.059	1.820	1.223
5/8	15.875	1.759	1.173	1.941	1.301	2.245	1.504
11/16	17.463	2.128	1.427	2.354	1.582	2.717	1.826
3/4	19.050	2.533	1.698	2.794	1.873	3.230	2.166
7/8	22.255	3.448	2.312	3.803	2.550	4.401	2.957
1	25.400	4.503	3.019	4.968	3.331	5.742	3.850
1 1/16	26.988	5.083	3.408	5.621	3.777	6.490	4.361
1 1/8	28.575	5.699	3.821	6.287	4.215	7.276	4.889
1 1/4	31.750	7.036	4.717	7.762	5.204	8.972	6.016
1 3/8	34.925	8.513	5.708	9.414	6.326	10.870	7.305
1 1/2	38.100	10.132	6.793	11.177	7.494	12.919	8.662
1 5/8	41.275	11.891	7.973	13.148	8.835	15.177	10.199
1 3/4	44.450	13.791	9.247	15.214	10.201	17.603	11.829
2	50.800	18.013	12.077	19.871	13.323	23.006	15.460
2 1/4	57.150	22.797	15.285	25.207	16.940	29.107	19.560
2 3/8	60.325	25.401	17.031	28.095	18.880	32.441	21.800
2 1/2	63.500	28.145	18.867	31.116	20.909	35.938	24.150
2 3/4	69.85	34.055	22.833	37.664	25.310	43.482	29.220
3	76.200	40.529	27.178	44.822	30.162	51.756	34.780
3 1/4	82.550	47.563	31.965	52.472	35.313	40.649	40.814
4	101.600	72.051	48.422	79.484	53.489	91.871	61.824

BARRAS Y VARILLAS DE COBRE ELECTROLITICO Y MAQUINABLE

Aleación N° 110 (Cobre Electrolítico ETP); N° 145 (Cobre Teluro) y N° 187 (Cobre Plomo) Según Normas ASTM B-187 y B-301